Edger Optimizer Technology

DK 90



Manual fed edger and gang circular resaw



Manual fed edger and gang circular resaw

with bottom arbor and up to 4 hydraulically variable moveable saw heads for edging and resawing of boards and cants





Clear pointers indicate the position of the saw heads and the pickers at the machine. Perfect board alignment by means of moveable laser lines.

The manual fed edger and gang circular resaw DK 90 is the perfect supplement to main break down machines such as sash gang saw or log bandmill in small and medium sized sawmills. In larger operations the DK 90 is used as a valuable side machine for versatile and flexible tasks.

The machine was refined over many years and stands today for high and everlasting reliability also under tough conditions.







Saw heads are positioned with hydraulic cylinders and maintenance-free sensors.




DK 90

Technical data

Туре		DK 90
Sawing height* Lumber length min. Lumber width unedged	mm m mm	15 – 120 (*Special unit: 160 mm) 1 80 – 900 (700)
Lumber width edged	mm	24 – 600
Machine opening max. Saw blade diameter max.	mm mm	1000 (800) 500
Saw arbor diameter Main drive motor size	mm kW	70 37 – 132 (@ 3000 rpm)
Feed drive motor Feed speed max.	kW m/min	5,5 – 7,5 100
Weight without drive motor Weight with drive motor (90 kW)	t t	approx. 4,5 approx. 5,0

Dimensions (in mm)



Due to constant product improvements or developments the illustrations and specifications contained in this brochure are subject to change without notice.